

WARRICK COUNTY HIGHWAY ENGINEER

107 West Locust St. Suite 208 - BOONVILLE, IN. 47601
PHONE (812) 897-6094 - FAX (812) 897-6109

Minimum Standards

I: Commercial Drive:

- 1.) 30' Throat Width
- 2.) 35' Radius
- 3.) Concrete 8" Reinforced (min. 3500 p.s.i.) Concrete on 6" Compacted Aggregate
- 4.) Asphalt 7" (1" Surface & 2 Layers of 3" base) on 6" of Compacted Aggregate

II: Utility Pull Off:

- 1.) 12' Throat Width
- 2.) 25' Tapers
- 3.) Concrete 6" Reinforced (min. 3500 p.s.i.) Concrete on 6" Compacted Aggregate
- 4.) Asphalt 7" (1" Surface & 2 Layers of 3" base) on 6" of Compacted Aggregate

All Commercial Driveway Entrance Standards are derived from the INDOT Driveway Permit Manual as adopted by the Warrick County Board of Commissioners.

All Commercial Driveway Permits shall be submitted in triplicate (3) containing a two-dimensional sketch with the following information:

- Plan View
- Cross Sectional View
- Certified by an Registered Indiana Engineer, Land Surveyor or Architect. Must have original signature and seal.
- Dollar amount for the cost of construction of said driveway in county road right-of-way.
- Drainage calculation to support size of drainage structure (if required).

All Commercial Drive Applications must include either a Performance Bond, Irrevocable Letter of Credit, Certified Check or surety to the Board of County Commissioners to cover the cost of the driveway or approach, unless applicant is applying for an Improvement Location Permit then the Area Plan Commission will require that the driveway be constructed or bonded prior to issuing an Improvement Location Permit/Building Permit.

Entrance conditions for subdivisions are reviewed during the submittal of Street and Drainage Construction Plans. Please refer to Ordinance Number 1998-14-Q of the current Subdivision Control Ordinance.