

ORIGINAL USPLS SURVEY: Corner established by Jacob Fowler, Dec., 1805 (missing notes).

COUNTY SURVEYOR'S BOOKS: Book 1 P. 96: John C. Frary WCS Mar. 30, 1858 Stone, marked" Book 3 P. 77: J.H.Wilke WCS Nov. 1905 "Pump sleeve formerly established for corner"

OTHER SURVEYS AND PLATS: "Corner Code System" card shows ref. from Bell Rd. Estates (man. not identified). "Corner Record" cards show 1977 reference to 1" IP taken from plat of Bell Terrace, and 1984 reference to 1-1/2" Pipe.

RR Spike (Punched) was found and tied in to Telephone Road Route Survey (Bernardin-Lochmueller & Assoc.) 2002.

VERIFICATION OF CORNER POSITION: September 2002: The railroad spike shown was found in place, its position consistent with the 1977 and 1984 Corner Record Card reference ties (+/- 0. 11 )

June, 2005: The railroad spike found in place, reference points found and measured accurate with 200' tape.

COMMENTS/RECOMMENDATIONS: Planned future improvements to Telephone Road may provide the opportunity to search beneath pavement level for an old stone or other evidence to further verify this position.

Perry E. Jones 9/26/02

Brian Schnur and Dan Grady 6/14/05