

CORNER HISTORY:

CORNER FILE CODE:
TfS-R9W-N-19

ORIGINAL USPLS SURVEY: Corner established by Jacob Fowler, Dec. 21(?), 1805 "Post".

COUNTY SURVEYOR'S BOOKS: Book 1 P. 21: Isaac Adams WCS Dec. 7, 1853 (Mon. not identified) Book 2 P. 45:

O.B.Pasco WCS May 5, 1886 "S. Stone marked S 23"

Book 4 P. 5: C. Warren Abbott WCS Jan. 28, 1946 "Iron Pin" (@ old estab. Fence to south, iron pins set 666.4'N, 66'E, and 132'E) OTHER SURVEYS AND PLATS: "Corner Record" card shows a 1973 reference (monument not identified). An Exempt Division by Danny K. Leek dated 5/11/93 shows a 5/8" iron rod.

1994 INDOT survey (K.E. Jackson) tied in and referenced a 5/8" rebar.

Location Control Route Survey for S.R. 261 by Alvin A. Paul (Doc. 1999R-007461) tied in and referenced a boat spike 6" below grade marking the corner (dimensions to corners east and west matched INDOT survey and D. Leek survey within 0.06').

VERIFICATION OF CORNER POSITION: September, 2002: The 5/8" rebar shown was found in place, consistent with reference ties from the 1994 K.E. Jackson route survey for INDOT.

Perry E. Jones 9170102